



# Technical Bulletin

PHENOMENAL BRANDS, Phenopatch Products  
A division of DAP Products Inc.  
2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-779-3265

Revised: 7/31/07

## Phenopatch™ Pre-Mixed Concrete Patch 5.5 fl. oz. Squeeze Tube

- For filling small cracks in basement walls, concrete steps, patios, sidewalks, and driveways
- Durable and non-shrinking
- Ready-to-use
- Easy water clean-up

**Packaging:** 5.5 fluid ounces (162 mL)  
**Color:** Gray  
**UPC Number:** 0 70798 32605 7

### Company Identification:

**Manufacturer:** PHENOMENAL BRANDS, Phenopatch Products, A division of DAP Products Inc.,  
2400 Boston St., Baltimore, Maryland 21224  
**Usage Information:** 410-779-3265 9:00 am to 7:00 pm EST.  
**Order Information:** 410-779-3265  
Also, visit the Phenopatch website at [www.phenopatch.com](http://www.phenopatch.com)

### Product Description:

**Phenopatch™ Pre-Mixed Concrete Patch** is a premium-grade, latex sealant specifically formulated to quickly repair small cracks in concrete and masonry. Forms a weather-resistant, watertight seal that helps prevent water and ice damage. Resists cracking and crumbling. Dries to a light color similar to new concrete and blends in with most types of masonry surfaces. Can be painted with most latex based paints. Safe, latex-based, easy water clean-up formula.

### Suggested Uses:

#### **Ideal for filling and sealing cracks in:**

- Basement Walls
- Sidewalks
- Concrete Steps
- Driveways
- Patios
- Other Concrete Surfaces

#### **Adheres to:**

- Concrete
- Mortar
- Stone
- Brick
- Masonry
- Cinder block
- Stucco
- Wood

- Other construction materials

**Performance Characteristics:**

- Ready to use – needs no mixing or additives.
- Offers excellent weatherability to resist UV light, rain, snow, and temperature extremes without cracking, bubbling or becoming brittle
- Provides a durable, long-lasting repair that is resistant to many chemicals, salt, grease and oil when fully cured.
- Water clean-up.

**Surface Preparation & Application:**

**FOR BEST RESULTS:**

- Concrete should be dry before applying.
- Not recommended for surfaces subject to vehicular traffic.
- Apply in temperatures above 40° F.
- Do not use below waterline.
- Do not use if rain or freezing temperatures are forecasted before full cure can occur (approximately 24 hours depending on temperature, humidity and depth of fill).

**INSTRUCTIONS:**

1. Surface must be clean & free of debris.
2. Remove cap & cut nozzle at a 45° angle to desired bead size.
3. If gap is deeper than 1/2", use backer rod.
4. Squeeze Concrete Patch into crack, pushing caulk ahead of nozzle.
5. A more uniform fill may be obtained by wetting a putty knife with water and tooling slightly.
6. Clean up excess with damp cloth before it skins over (30 mins).
7. Allow to dry at least 2 hrs. (longer in cool/humid conditions) before painting with latex or oil-based paints.
8. Allow to dry and fully cure for at least 24 hrs, depending on temperature, humidity and depth of fill before moisture exposure.
9. Reseal tube. Store away from extreme heat or cold.

**Physical & Chemical Characteristics:**

Vehicle:	Acrylic Polymer
Volatile:	Water
Filler:	Calcium Carbonate, Sand
Solids:	77% ±1% by weight
Weight Per Gallon:	12.6 lbs. ±0.02 lbs.
Temperature Application Range:	40°F Minimum
Temperature Service Range:	-30°F to 150° F
Freeze/Thaw Stability:	Passes 5 Cycles
Consistency:	Smooth, Squeeze Tube
Applications:	Interior/Exterior
Shelf Life:	1 Year
Coverage:	30 linear feet at 3/16" diameter bead
MSDS No:	000 10040 005

**Clean Up & Storage:**

Clean up excess with damp cloth before it skins over (30 mins). Dried material must be cut or scraped away. Wash tools immediately after use with water. Store in a cool, dry place away from extreme heat or cold.

**Safety:**

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS sheet by calling 410-779-3265.

**Satisfaction Guaranteed:** If not satisfied with product's performance when used as directed, return used container and sales receipt to PHENOMENAL BRANDS, Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. PHENOMENAL BRANDS will not be liable for incidental or consequential damages.