



TECHNICAL DATA SHEET

1/25/2018

DAP® PHENOPATCH® Spackling Paste



Product Description: DAP® Phenopatch® All Purpose Spackling Paste is a ready mixed, easy-to-use patching material used to fill holes and cracks and treat surfaces prior to painting. The product has a smooth working consistency, dries quickly, is non-shrinking and sands easily. Recommended for interior use only.

Suggested Uses:

Ideal for filling and concealing small cracks, nail holes and blemishes in:

- Drywall

Available In:

SKU #	Description	Size	Package Type	Case Pack	Color
7079810222	DAP® Spackling Paste	8 Fl. Oz. (236 mL)	Tub	PK	White
7079810224	DAP® Spackling Paste	32 Fl. Oz (946 mL)	Tub	PK	White
7079876859	DAP® Spackling Paste	128 Fl. Oz (3.78 L)	Tub	PK	White

Surface Preparation & Application Instructions:

- Surface must be clean, dry and free of dust and particles.
- Use sandpaper to dull glossy surface before repairing.
- Stir thoroughly before use.
- Apply with a clean putty knife.
- For a smoother finish, dip putty knife in water and lightly smooth spackling.
- For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
- Spackling Paste can be sanded or painted in 1 to 5 hours after application, depending on temperature, humidity and depth of fill.
Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

Cleanup & Storage Recommendations:

- Wash tools immediately after use with water.
- Be sure container is closed and tightly sealed.
- Store in a cool, dry place.



TECHNICAL DATA SHEET

Typical Physical & Chemical Characteristics:

Consistency	Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	14.8 pounds
Solids	71%
Application Temperature	50°F minimum
Service Temperature	0°F to 150°F
Shelf Life	1 year
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	2 to 5 hours depending on temperature, humidity and depth of fill
SDS Number	00079944005

Safety Information:

Contains: Crystalline silica. Sanding of this product may generate dust. Inhalation of dust may cause adverse pulmonary and respiratory effects. May cause eye and skin irritation. Do not breathe dust. Use only with adequate ventilation. Ensure fresh air entry. Wet sanding is recommended to reduce dust exposure. When sanding, wear a NIOSH-approved dust mask. Harmful if swallowed. Do not ingest. Avoid contact with eyes, skin and clothing. Wear gloves and safety glasses. Close container after use. Wash thoroughly after handling.

FIRST AID: SKIN: Wash thoroughly. EYE: Immediately flood with large quantities of water. INHALATION: Remove to fresh air. INGESTION: DO NOT INDUCE VOMITING. Get medical attention if complications arise from any exposure. **For emergencies,** call your poison control center at 1-800-222-1222. See Safety Data Sheet (SDS) for additional information. For an SDS, contact your supplier or visit phenopatch.com.

KEEP OUT OF REACH OF CHILDREN.

Warranty Information:

- If product fails to perform as directed, within one year from the date of purchase, call 1-888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund.
- DAP will not be responsible for incidental or consequential damages.

Disclaimer:

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.



TECHNICAL DATA SHEET

Company Information:

Manufacturer: PHENOMENAL BRANDS, Phenopatch Products, A division of DAP Products Inc.
2400 Boston Street, Baltimore, MD 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339

Fax Number: 410-558-1068

Also visit the Phenopatch website at phenopatch.com.